

```
#ifndef GGCONSTANTS_H
#define GGCONSTANTS_H
```

```
const double ggFourPi = 12.566371; /* needs more digits */
const double ggTwoPi = 6.2831853; /* needs more digits */
const double ggPi = 3.14159265358979323846;
const double ggHalfPi = 1.57079632679489661923;
const double ggThirdPi = 1.0471976; /* needs more digits */
const double ggQuarterPi = 0.78539816; /* needs more digits */
const double ggInversePi = 0.31830989;
const double ggSqrtTwo = 1.4142135623730950488;
const double ggInverseSqrtTwo = 0.70710678;
const double ggSqrtThree = 1.7320508075688772935;
const double ggSqrtFive = 2.2360679774997896964;
const double ggE = 2.718281828459045235360287;
```

```
const double ggRad = 57.29577951308232;
```

```
#ifdef sun
const double ggInfinity = 1.0e10;
#else
#include <float.h>
const double ggInfinity = DBL_MAX;
#endif
```

```
#ifndef M_PI
#define M_PI ggPi
#endif
```

```
const double ggBigEpsilon = 0.0001;
const double ggEpsilon = 0.000001;
const double ggSmallEpsilon = 0.000000001;
const double ggTinyEpsilon = 0.000000000001;
```

```
const double ggColorRatio = 0.0039215686274509803;
```

```
typedef
```

```
#define ggMin(x,y) (x < y) ? x : y
#define ggMax(x,y) (x > y) ? x : y
```

APPENDIX PAGE 1

APPENDIX PAGE 2

```

/* Includes required */
#ifndef WINDOWS
#include <windows.h>
#endif

#include <GL/gl.h>
#include <GL/glut.h>
#include <stdio.h>
#include <math.h>
#ifdef USE_NETPBM
#include <ppm.h>
#endif

/**
 * something because of windows.
 */
void _eprintf() {
}

/**
 * our data structure of choice
 */
typedef struct obj {
    /* other parameters */
    float matrix[16];

    /* view angle */
    float viewangle;

    /* aspect ratio */
    float aspect;

    /* z of the camera */
    float tz;

    /* ry of the camera */
    float ry;
} Obj;

/* hold the display lists for textures */
typedef struct texture {
    int tex1;
    int tex2;
} Texture;

/**
 * our global variables
 */
/* camera settings */
Obj scene;

/* texture stuff */
Texture dei;
Texture* current_texture = &dei;

/* track the next display list number */
int nextDLnum = 2;

/* stuff for lighting */
float lightPos[4] = {2.0, 4.0, 2.0, 0};
float lightDir[4] = {0, 0, 1.0, 1.0};
float lightAmb[4] = {0.3, 0.3, 0.3, 1.0};
float lightDiff[4] = {0.6, 0.6, 0.6, 1.0};
float lightSpec[4] = {0.6, 0.6, 0.6, 1.0};
float clipDistance = 2.14;

```

```

int left, right, parent;
int width, height;
#ifdef USE_NETPBM
pixel** ppmPixels = 0;
#endif
GLubyte* sgiPixels = 0;
FILE* commands;
int doTakeSnapshot = 0;

#define HEMISPHERE 1
void createHemisphere(int listNum, int numPts, int geom);
void draw_left();
void draw_right();
void Key(unsigned char,int,int);

/**
 * read the frame buffer and write out a ppm file
 */
void takeSnapshot() {
#ifdef USE_NETPBM
    static int shotNum = 0;
    FILE* file;
    char name[50];
    int index, i, j;

    /* draw everything again */
    draw_right();
    glFlush();
    draw_left();
    glFlush();

    /* read the pixels from the frame buffer */
    glReadPixels(0, 0, width, height, GL_RGB, GL_UNSIGNED_BYTE, sgiPixels);

    /* convert then to the ppm */
    index = 0;
    for (i = height - 1; i >= 0; i--) {
        for (j = 0; j < width; j++) {
            PPM_ASSIGN(ppmPixels[i][j],
                sgiPixels[index],
                sgiPixels[index + 1],
                sgiPixels[index + 2]);
            index += 3;
        }
    }

    /* open a file */
    sprintf(name, "%d.ppm", shotNum);
    shotNum++;
    file = fopen(name, "w");

    /* write the ppm file */
    ppm_writeppm(file, ppmPixels, width, height, 255, 0);

    /* close the file */
    fclose(file);
#endif
}

/**
 * Read in the ppm files and create display lists for a texture
 * returns the dimension of the image
 */
void readTexture(Texture* t, char* file1, char* file2) {
#ifdef USE_NETPBM

```

APPENDIX PAGE 3

```

FILE *fp1, *fp2;
int cols, rows, i, j, index;
pixel **map1, **map2;
GLubyte *tex1, *tex2;
pixval maxval;

/* open the files */
fp1 = fopen(file1, "r");
fp2 = fopen(file2, "r");
if (!fp1) {
    printf(stderr, "Couldn't open %s\n", file1);
}
if (!fp2) {
    printf(stderr, "Couldn't open %s\n", file2);
}

/* read the ppm files */
map1 = ppm_readppm(fp1, &cols, &rows, &maxval);
printf(stderr, "fs: rows = %d \t cols = %d\n", file1, rows, cols, maxval);
map2 = ppm_readppm(fp2, &cols, &rows, &maxval);
printf(stderr, "fs: rows = %d \t cols = %d\n", file2, rows, cols, maxval);

/* convert them */
tex1 = malloc(sizeof(GLubyte) * rows * cols * 3);
tex2 = malloc(sizeof(GLubyte) * rows * cols * 3);
index = 0;
for (i = 0; i < rows; i++) {
    for (j = 0; j < cols; j++) {
        /* R */
        tex1[index] = PPM_GETR(map1[i][j]);
        tex2[index] = PPM_GETR(map2[i][j]);
        index++;

        /* G */
        tex1[index] = PPM_GETG(map1[i][j]);
        tex2[index] = PPM_GETG(map2[i][j]);
        index++;

        /* B */
        tex1[index] = PPM_GETB(map1[i][j]);
        tex2[index] = PPM_GETB(map2[i][j]);
        index++;
    }
}

/* create the textures in the left */
glutSetWindow(left);
/* new display list */
glNewList(nextDlnum, GL_COMPILE);
t->tex1 = nextDlnum;
nextDlnum++;
glTexImage2D(GL_TEXTURE_2D, 0, 3, cols, rows, 0, GL_RGB, GL_UNSIGNED_BYTE,
    tex1);
glEndList();

/* new display list */
glNewList(nextDlnum, GL_COMPILE);
t->tex2 = nextDlnum;
nextDlnum++;
glTexImage2D(GL_TEXTURE_2D, 0, 3, cols, rows, 0, GL_RGB, GL_UNSIGNED_BYTE,
    tex2);
glEndList();

/* create the textures in the right */
glutSetWindow(right);

```

```

/* new display list */
glNewList(t->tex1, GL_COMPILE);
glTexImage2D(GL_TEXTURE_2D, 0, 3, cols, rows, 0, GL_RGB, GL_UNSIGNED_BYTE,
    tex1);
glEndList();

/* new display list */
glNewList(t->tex2, GL_COMPILE);
glTexImage2D(GL_TEXTURE_2D, 0, 3, cols, rows, 0, GL_RGB, GL_UNSIGNED_BYTE,
    tex2);
glEndList();

free(tex1);
free(tex2);
free(map1);
free(map2);
#endif
}

/*
 * this will initialize the display lists for the objects
 */
void initialize_objects(int argc, char**argv) {
    float tnp[4];

    /* read in the texture */
    readTexture(&def, argv[1], argv[2]);

    /* create hemisphere left */
    glutSetWindow(left);
    createHemisphere(1, 50, GL_TRIANGLE_STRIP);

    /* create hemisphere right */
    glutSetWindow(right);
    createHemisphere(1, 50, GL_TRIANGLE_STRIP);

    /* scene */
    scene.viewangle = 50;
    scene.tz = 0;
}

void display_parent() {
    /* clear the screen */
    glClear(GL_COLOR_BUFFER_BIT | GL_DEPTH_BUFFER_BIT);
}

void draw_left() {
    float tnp[4];

    /* clear the screen */
    glutSetWindow(left);
    glClear(GL_COLOR_BUFFER_BIT | GL_DEPTH_BUFFER_BIT);

    /* adjust for scene orientation */
    glMatrixMode(GL_PROJECTION);
    glLoadIdentity();
    gluPerspective(scene.viewangle, scene.aspect, 0.1, 10.0);
    glRotatef(scene.ry, 1, 0, 0);
    glTranslatef(0, 0, scene.tz);

    /* draw our models */
    glMatrixMode(GL_MODELVIEW);
    glPushMatrix();

```

APPENDIX PAGE 4

```

/* now draw the hemisphere */
glEnable(GL_TEXTURE_2D);
glColor3f(.5, .5, .5);
glCallList(current_texture->tex1);
glCallList(HEMISPHERE);

glRotatef(180, 0.0, 0.0, 1.0);
glColor3f(1, 1, 1);

glCallList(current_texture->tex2);
glCallList(HEMISPHERE);
glPopMatrix();

fprintf(stderr, "left - %s\n", gluErrorString(glGetError()));
}

void display_left()
{
    draw_left();
    glutSwapBuffers();
}

void draw_right() {
    float tmp[4];
    float height;

    /* clear the screen */
    glutSetWindow(right);
    glClear(GL_COLOR_BUFFER_BIT | GL_DEPTH_BUFFER_BIT);

    /* setup the camera */
    glMatrixMode(GL_PROJECTION);
    glLoadIdentity();
    gluPerspective(45, scene.aspect, clipDistance, 10.0);
    glTranslatef(0, 0, -3);
    glRotatef(15, 1, 2, 0);
    glRotatef(15, 0, 1, 0);
    glRotatef(15, 0, 1, 0);
    glDisable(GL_TEXTURE_2D);

    /* draw our models */
    glMatrixMode(GL_MODELVIEW);
    glPushMatrix();

    /* draw a cube for the camera */
    glPushMatrix();
    glLoadIdentity();
    glRotatef(180, 1, 0, 0);
    glRotatef(-scene.ry, 1, 0, 0);
    glTranslatef(0, 0, scene.tz);

    tmp[0] = tmp[1] = tmp[2] = .8;
    tmp[3] = 1;
    glMaterialfv(GL_FRONT_AND_BACK, GL_SPECULAR, tmp);
    glMaterialfv(GL_FRONT_AND_BACK, GL_SHININESS, 0.0);
    glMaterialfv(GL_FRONT_AND_BACK, GL_AMBIENT_AND_DIFFUSE, tmp);
    glutSolidCube(1);

    /* now the light */
    tmp[0] = tmp[1] = tmp[2] = 0;
    tmp[3] = 1;
    glLightfv(GL_LIGHT1, GL_POSITION, tmp);
    glLightf(GL_LIGHT1, GL_SPOT_CUTOFF, scene.viewangle / 2);
    tmp[0] = tmp[1] = 0; tmp[2] = 1; tmp[3] = 1;
    glLightfv(GL_LIGHT1, GL_SPOT_DIRECTION, tmp);

    /* draw a cone for the view frustrum */

```

```

glLoadIdentity();
height = 1 - scene.tz;
glRotatef(-scene.ry, 1, 0, 0);
glRotatef(45, 0, 0, 1);
glTranslatef(0, 0, -1);
tmp[0] = tmp[1] = .8;
tmp[2] = 0;
tmp[3] = 1.0;
glMaterialfv(GL_FRONT_AND_BACK, GL_SPECULAR, tmp);
glMaterialfv(GL_FRONT_AND_BACK, GL_SHININESS, 0.0);
glMaterialfv(GL_FRONT_AND_BACK, GL_AMBIENT_AND_DIFFUSE, tmp);
glutWireCone(tan(scene.viewangle * 3.14 / 360.0) * height, height, 10, 4);
glPopMatrix();

```

```

/* draw one half of the sphere */
tmp[0] = tmp[1] = tmp[2] = tmp[3] = 0;
glMaterialfv(GL_FRONT_AND_BACK, GL_SPECULAR, tmp);
glMaterialfv(GL_FRONT_AND_BACK, GL_SHININESS, 0.0);
glEnable(GL_TEXTURE_2D);
tmp[0] = tmp[1] = tmp[2] = tmp[3] = 1.0;
glMaterialfv(GL_FRONT_AND_BACK, GL_AMBIENT_AND_DIFFUSE, tmp);
glCallList(current_texture->tex1);
glCallList(HEMISPHERE);
glPopMatrix();

```

```

/* draw the other half */
glRotatef(180, 0, 0, 1);
glCallList(current_texture->tex2);
glCallList(HEMISPHERE);
glPopMatrix();
fprintf(stderr, "right - %s\n", gluErrorString(glGetError()));
}

```

```

void display_right() {
    draw_right();
    glutSwapBuffers();
}

```

```

/*
 * Handle Menu
 */
#define M_QUIT 1
void Select(int value)
{
    switch (value) {
        case M_QUIT:
            exit(0);
            break;
    }
    glutPostRedisplay();
}

void create_menu() {
    glutCreateMenu(Select);
    glutAddMenuEntry("Quit", M_QUIT);
    glutAttachMenu(GLUT_RIGHT_BUTTON);
}

```

```

/* Initializes hiding model */
void init_left()
{
    glEnable(GL_DEPTH_TEST);
    glShadeModel(GL_SMOOTH);

    /* texture stuff */
    glEnable(GL_TEXTURE_2D);

```

APPENDIX PAGE 4

```

glPixelStorei(GL_UNPACK_ALIGNMENT, sizeof(GLubyte));
glTexEnvf(GL_TEXTURE_ENV, GL_TEXTURE_ENV_MODE, GL_DECAL);
glTexParameterf(GL_TEXTURE_2D, GL_TEXTURE_WRAP_S, GL_CLAMP);
glTexParameterf(GL_TEXTURE_2D, GL_TEXTURE_WRAP_T, GL_CLAMP);
glTexParameterf(GL_TEXTURE_2D, GL_TEXTURE_MAG_FILTER, GL_NEAREST);
glTexParameterf(GL_TEXTURE_2D, GL_TEXTURE_MIN_FILTER, GL_NEAREST);
}

void init_right() {
    glEnable(GL_DEPTH_TEST);
    glShadeModel(GL_SMOOTH);

    /* texture stuff */
    glEnable(GL_TEXTURE_2D);
    glPixelStorei(GL_UNPACK_ALIGNMENT, sizeof(GLubyte));
    glTexEnvf(GL_TEXTURE_ENV, GL_TEXTURE_ENV_MODE, GL_MODULATE);
    glTexParameterf(GL_TEXTURE_2D, GL_TEXTURE_WRAP_S, GL_CLAMP);
    glTexParameterf(GL_TEXTURE_2D, GL_TEXTURE_WRAP_T, GL_CLAMP);
    glTexParameterf(GL_TEXTURE_2D, GL_TEXTURE_MAG_FILTER, GL_NEAREST);
    glTexParameterf(GL_TEXTURE_2D, GL_TEXTURE_MIN_FILTER, GL_NEAREST);

    /* for blending */
    glEnable(GL_BLEND);
    glBlendFunc(GL_SRC_ALPHA, GL_ONE_MINUS_SRC_ALPHA);

    /* lighting */
    glEnable(GL_LIGHTING);
    glEnable(GL_LIGHT0);
    glLightfv(GL_LIGHT0, GL_POSITION, lightPos);
    glLightfv(GL_LIGHT0, GL_AMBIENT, lightAmb);
    glLightfv(GL_LIGHT0, GL_DIFFUSE, lightDiff);
    glLightfv(GL_LIGHT0, GL_SPECULAR, lightSpec);

    glEnable(GL_LIGHT1);
    lightAmb[2] = 0;
    lightAmb[0] = lightAmb[1] = -.8;
    lightAmb[3] = 1;
    glLightfv(GL_LIGHT1, GL_AMBIENT, lightAmb);
    glLightfv(GL_LIGHT1, GL_DIFFUSE, lightDiff);
    glLightfv(GL_LIGHT1, GL_SPECULAR, lightSpec);
}

/*
 * Called when the window is first opened and whenever
 * the window is reconfigured (moved or resized).
 */
void myReshape(int w, int h)
{
    /* set width and height */
    width = w;
    height = h;

    /* define the viewport */
    glViewport (0, 0, w, h);
    scene.aspect = 1.0*(GLfloat)w/2/(GLfloat)h;

    /* reshape the subwindows */
    /* first left */
    glutSetWindow(left);
    glutReshapeWindow(w/2, h);

    /* now right */
    glutSetWindow(right);
    glutReshapeWindow(w/2, h);
    glutPositionWindow(w/2, 0);
}

```

```

/* allocate memory for the snapshot thingy */
if (sglPixels) {
    free(sglPixels);
}
sglPixels = malloc(sizeof(GLubyte) * width * height * 3);

#ifdef USE_NETPM
if (ppmPixels) {
    ppm_freearray(ppmPixels, height);
}
ppmPixels = ppm_alloccarray(width, height);
#endif

/**
 * an idle function to do automate things
 */
#define MOVE 0
#define SNAP 1
void idleSnapshots() {
    static moveOrSnap = MOVE;

    if (moveOrSnap == MOVE) {
        /* next command */
        Key('z', 0, 0);
        moveOrSnap = SNAP;
    } else {
        /* snapshot */
        Key('s', 0, 0);
        moveOrSnap = MOVE;
    }
}

/**
 * Rotate both displays
 */
void doRotate(float amt, float x, float y, float z) {
    glutSetWindow(left);
    glRotatef(amt, x, y, z);
    glutSetWindow(right);
    glRotatef(amt, x, y, z);
}

/*
 * Keyboard handler
 */
void
Key(unsigned char key, int x, int y)
{
    int keyInt;
    float matrix1[16];
    float matrix2[16];
    glutSetWindow(left);
    glMatrixMode(GL_MODELVIEW);
    glGetFloatv(GL_MODELVIEW_MATRIX, matrix1);
    glLoadIdentity();
    glutSetWindow(right);
    glMatrixMode(GL_MODELVIEW);
    glGetFloatv(GL_MODELVIEW_MATRIX, matrix2);
    glLoadIdentity();

    /* check for read command */
    if (key == 'r') {
        fscanf(commands, "%d", &keyInt);
    }
}

```

```

key = (char) keyInt;
fprintf(stderr, "read %d - %c\n", key, key);
)

```

```

printf("%d\n", key);
fflush(stdout);
switch (key) {
case '!':

```

```

/* register idle function */
glutSetWindow(parent);
glutIdleFunc(idleSnapshots);
break;

```

```

case 13:
/* press enter - take snapshot */
doTakeSnapshot = 1;
break;

```

```

case 'c':
clipDistance += .02;
break;

```

```

case 'C':
clipDistance += .02;
break;

```

```

case 'y':
printf("ry = %f\n", scene.ry);
scene.ry += 5;
break;

```

```

case 'Y':
scene.ry += 5;
break;

```

```

case 'z':
scene.tz += .02;
break;

```

```

case 'Z':
scene.tz += .02;
break;

```

```

case 'a':
scene.viewangle += 1;
break;

```

```

case 'A':
scene.viewangle += 1;
break;

```

```

case 55:
doRotate(-5, 0.0, 0.0, 1.0);
break;

```

```

case 57:
doRotate(5, 0.0, 0.0, 1.0);
break;

```

```

case 52:
doRotate(-5, 0.0, 1.0, 0.0);
break;

```

```

case 54:
doRotate(5, 0.0, 1.0, 0.0);
break;

```

```

case 56:
doRotate(5, 1.0, 0.0, 0.0);
break;

```

```

case 50:
doRotate(-5, 1.0, 0.0, 0.0);
break;

```

```

case '?':
fprintf(stderr, "arrows - rotate the sphere\n");
fprintf(stderr, "A/A viewangle\n");
fprintf(stderr, "C/C adjust clip plane in right window\n");
fprintf(stderr, "z/Z camera position\n");
fprintf(stderr, "Escape quits\n");

```

APPENDIX PAGE 4

```

break;
case 27: /* Esc will quit */
exit(1);
break;
default:
fprintf(stderr, "Unbound key - %d\n", key);
break;
)
fprintf(stderr, "clip = %f viewangle = %f zdepth = %f\n",
clipDistance, scene.viewangle, scene.tz);
glutSetWindow(left);
glMultMatrixf(matrix1);
glutPostRedisplay();
glutSetWindow(right);
glMultMatrixf(matrix2);
glutPostRedisplay();

/* check for snapshot */
if (doTakeSnapshot) {
takeSnapshot();
doTakeSnapshot = 0;
}
)

```

```

/*
* Main Loop
* Open window with initial window size, title bar,
* RGBA display mode, and handle input events.
*/

```

```

int main(int argc, char** argv)
{
glutInit(&argc, argv);
glutInitDisplayMode(GLUT_DOUBLE | GLUT_RGBA);

```

```

/* create the parent window */
parent = glutCreateWindow(argv[0]);
width = 512; height = 256;
glutReshapeWindow(width, height);
glutKeyboardFunc(Key);
glutReshapeFunc(myReshape);
glutDisplayFunc(display_parent);
create_menu();

```

```

/* left window */
left = glutCreateSubWindow(parent, 0, 0, width / 2, height);
glutKeyboardFunc(Key);
glutDisplayFunc(display_left);
create_menu();
init_left();

```

```

/* right window */
right = glutCreateSubWindow(parent, width / 2, 0, width / 2, height);
glutKeyboardFunc(Key);
glutDisplayFunc(display_right);
create_menu();
init_right();

```

```

/* create objects */
initialize_objects(&argc, argv);

```

```

/* open file */
if (argc == 4) {
fprintf(stderr, "Opening %s for commands\n", argv[3]);
commands = fopen(argv[3], "r");
}
glutMainLoop();
}

```

APPENDIX PAGE 7

```

/*****
/* warp.c
*****/

#include <math.h>
#include "ggConstants.h"

/*
 * This function takes a point in the unit square, and maps it to
 * a point on the unit hemisphere.
 *
 * Copyright 1994 Kenneth Chiu
 *
 * This code may be freely distributed and used for any purpose, commercial
 * or non-commercial as long as attribution is maintained.
 */
void
map(double x, double y, double *x_ret, double *y_ret, double *z_ret) {

    double xx, yy, offset, theta, phi;

    x = 2*x - 1;
    y = 2*y - 1;

    if (y > -x) {          /* Above y = -x */
        if (y < x) {        /* Below y = x */
            xx = x;
            if (y > 0) {     /* Above x-axis */

                cerr<<"Octant 1 ";

                offset = 0;
                yy = y;

            } else {         /* Below and including x-axis */
                cerr<<"Octant 8 ";
                offset = (7*ggPi)/4;
                yy = x + y;
            }
        } else {            /* Above and including y = x */
            xx = y;
            if (x > 0) {     /* Right of y-axis */

                cerr<<"Octant 2 ";

                offset = ggPi/4;
                yy = (y - x);
            } else {         /* Left of and including y-axis */

                cerr<<"Octant 3 ";

                offset = (ggTwoPi)/4;
                yy = -x;
            }
        }
    } else {                /* Below and including y = -x */
        if (y > x) {        /* Above y = x */
            xx = -x;
            if (y > 0) {     /* Above x-axis */

                cerr<<"Octant 4 ";

                offset = (3*ggPi)/4;
                yy = -x - y;
            } else {         /* Below and including x-axis */

```

```

                cerr<<"Octant 5 ";

                offset = (ggFourPi)/4;
                yy = -y;
            } else {        /* Below and including y = x */
                xx = -y;
                if (x > 0) { /* Right of y-axis */

                    cerr<<"Octant 7 ";

                    offset = (6*ggPi)/4;
                    yy = x;
                } else {     /* Left of and including y-axis */
                    if (y != 0) {

                        cerr<<"Octant 6 ";

                        offset = (5*ggPi)/4;
                        yy = x - y;
                    } else {

                        cerr<<"Origin ";

                        *x_ret = 0;
                        *y_ret = 1;
                        *z_ret = 0;
                        return;
                    }
                }
            }
        }

        theta = acos(1 - xx*xx);
        phi = offset + (ggPi/4)*(yy/xx);

        *x_ret = sin(theta)*cos(phi);
        *y_ret = cos(theta);
        *z_ret = sin(theta)*sin(phi);
    }

    /*
     * This function takes a point in the unit hemisphere, and maps it to
     * a point on the unit square.
     *
     * Copyright 1994 Kenneth Chiu and Kurt Zimmerman
     *
     * This code may be freely distributed and used for any purpose, commercial
     * or non-commercial as long as attribution is maintained.
     */
    void
    unmap(double x, double y, double z, double *x_ret, double *y_ret)
    {
        double xx, yy, offset, theta, phi;

        theta = acos(y);

        if (theta < .0000001) /* vertical center */
        {
            *x_ret = 0.5;
            *y_ret = 0.5;
            return;
        }
        else

```

```

double cosphi,sinphi;
cosphi = x/sin(theta);
cosphi = ggMin(cosphi, 1.0); /* hack for now */
cosphi = ggMax(cosphi, -1.0);
sinphi = z/sin(theta);
sinphi = ggMin(sinphi, 1.0); /* hack for now */
sinphi = ggMax(sinphi, -1.0);

```

```

if(sinphi >= 0 )
    phi = acos(cosphi);
else if (sinphi < 0 && cosphi< 0)
    phi = -acos(cosphi);
else
    phi = asin(sinphi);

```

```
xx = sqrt(1 - y);
```

```
if(phi < -(3 * M_PI/4))
```

```

{
    /* cerr<<"5th octant ";*/
    yy = ((phi + M_PI * xx)/(M_PI/4));
    *x_ret = -xx;
    *y_ret = -yy;
}

```

```
else if(phi < -M_PI/2)
```

```

{
    /*cerr<<"6th octant ";*/
    yy = ((phi + (3*M_PI/4)) * xx)/(M_PI/4);
    *y_ret = -xx;
    *x_ret = *y_ret + yy;
}

```

```
else if(phi < -(M_PI/4))
```

```

{
    /*cerr<<"7th octant ";*/
    yy = ((phi + M_PI/2) * xx)/(M_PI/4);
    *x_ret = yy;
    *y_ret = -xx;
}

```

```
else if(phi < 0)
```

```

{
    /*cerr<<"8th octant ";*/
    yy = ((phi + M_PI/4) * xx)/(M_PI/4);
    *x_ret = xx;
    *y_ret = yy - *x_ret;
}

```

```
else if(phi < (M_PI/4))
```

```

{
    /*cerr<<"1st octant ";*/
    yy = ((phi) * xx)/(M_PI/4);
    *x_ret = xx;
    *y_ret = yy;
}

```

```
else if(phi < M_PI/2)
```

```

{
    /*cerr<<"2nd octant ";*/
    yy = ((phi - M_PI/4) * xx)/(M_PI/4);
    *y_ret = xx;
    *x_ret = *y_ret - yy;
}

```

```
else if(phi < 3*M_PI/4)
```

```

{
    /*cerr<<"3rd octant ";*/
    yy = ((phi - M_PI/2) * xx)/(M_PI/4);
    *x_ret = -yy;
}

```

```
*y_ret = xx;
```

```

}
else
{

```

```
/*cerr<<"4th octant ";*/
```

```

offset = 3*M_PI/4;
yy = ((phi - offset) * xx)/(M_PI/4);
*x_ret = -xx;
*y_ret = -yy - *x_ret;
}

```

```

}
*y_ret = (*y_ret + 1)/(2 + ggEpsilon);
*x_ret = (*x_ret + 1)/(2 + ggEpsilon);

```

APPENDIX PAGE 8


```
/*.....*/  
/* warp.h */  
/*.....*/
```

```
#ifndef WARP_DOT_H  
#define WARP_DOT_H
```

```
void map(double x, double y, double *x_ret, double *y_ret, double *z_ret);  
void unmap(double x, double y, double z, double *x_ret, double *y_ret);
```

```
#endif
```

APPENDIX PAGE 9